


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 300 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.3$	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 168.41 lm/W
MODEL	UFO-150W-120D	Imax(cd)	8099	S/MH(C0/180)	1.33	
NOMINAL POWER(W)	147	LOR(%)	100.0	S/MH(C90/270)	1.32	
RATED VOLTAGE(V)	230	TOTAL FLUX(lm)	24756	η UP,DN(C0-180)	0.0,51.6	
NOMINAL FLUX(lm)	24756.3	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,48.4	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.50	
TEST VOLTAGE(V)	229.2	η down(%)	100.0	CIBSE SHR MAX	1.50	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.400m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum, lamp
10	8030	8019	7970	7974					0- 10	768.1	768.1	3.1,3.1
20	7743	7714	7602	7632					10- 20	2222	2990	12.1,12.1
30	7224	7183	7015	7057					20- 30	3425	6414	25.9,25.9
40	6465	6411	6195	6245					30- 40	4226	10641	43,43
50	5470	5399	5133	5199					40- 50	4507	15147	61.2,61.2
60	4237	4149	3841	3922					50- 60	4194	19341	78.1,78.1
70	2787	2706	2369	2453					60- 70	3284	22625	91.4,91.4
80	1059	950.0	589.6	684.7					70- 80	1821	24446	98.7,98.7
90	105.4	105.4	77.61	77.50					80- 90	310.7	24756	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:chen xue chang
 Test Date:2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity:65.0%
 Test Distance:7.400m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\varnothing 300 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\varphi 0.3$	PROTECTION ANGLE:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	.00	.96	1.02	.98	.94	.97	.94	.91	.93	.91	.88	.90	.88	.86	.84
2.0	.90	.83	.77	.88	.82	.77	.85	.79	.75	.81	.77	.73	.78	.75	.71	.69
3.0	.79	.71	.64	.77	.70	.63	.74	.68	.62	.72	.66	.61	.69	.64	.60	.58
4.0	.70	.61	.54	.68	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.45	.57	.50	.45	.55	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.44	.39	.50	.44	.39	.37
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.47	.40	.35	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.43	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.25	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.400m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 300 \times H150mm$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.3$	PROTECTION ANGLE:

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.309	.176	.056	.302	.172	.055	.289	.166	.053	.276	.159	.051	.265	.154	.050		
2.0	.294	.161	.049	.288	.158	.049	.276	.153	.048	.265	.149	.047	.255	.144	.045		
3.0	.273	.145	.043	.267	.143	.043	.257	.139	.042	.247	.136	.042	.238	.132	.041		
4.0	.252	.131	.039	.247	.129	.038	.238	.126	.038	.229	.123	.037	.221	.120	.037		
5.0	.233	.119	.034	.229	.117	.034	.220	.115	.034	.213	.112	.033	.206	.110	.033		
6.0	.216	.108	.031	.212	.107	.031	.205	.105	.031	.198	.103	.030	.192	.101	.030		
7.0	.201	.099	.028	.198	.098	.028	.191	.097	.028	.185	.095	.028	.179	.093	.027		
8.0	.188	.092	.026	.185	.091	.026	.179	.089	.025	.173	.088	.025	.168	.086	.025		
9.0	.176	.085	.024	.173	.084	.024	.168	.083	.024	.163	.082	.023	.158	.080	.023		
10.0	.165	.079	.022	.163	.079	.022	.158	.077	.022	.153	.076	.022	.149	.075	.022		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.134	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.173	.132	.098	.148	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.165	.114	.074	.141	.099	.064	.097	.069	.045	.056	.040	.026	.018	.013	.009	
4.0	.158	.101	.058	.135	.087	.050	.093	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.150	.091	.047	.129	.078	.041	.089	.055	.029	.051	.032	.017	.017	.011	.006	
6.0	.143	.082	.039	.123	.071	.034	.085	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.136	.075	.033	.117	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.060	.025	.077	.042	.018	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.106	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.060	.022	.102	.053	.019	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:chen xue chang
Test Date:2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:7.400m [K=1.0000]
Remarks:

Uncorrected UGR Table

NAME: LED High Bay					TYPE:					WEIGHT:				
DIM.: $\phi 300 \times H150\text{mm}$					SPEC.:					SERIAL No.:				
MFR.:					SUR.: $\phi 0.3$					PROTECTION ANGLE:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					29.8	31.4	30.1	31.6	31.8	29.8	31.3	30.0	31.5	31.7
3H					31.5	33.0	31.8	33.2	33.4	31.4	32.9	31.7	33.1	33.3
4H					32.2	33.6	32.6	33.8	34.1	32.1	33.5	32.4	33.7	34.0
6H					32.7	33.9	33.0	34.2	34.5	32.5	33.8	32.8	34.0	34.3
8H					32.7	34.0	33.1	34.3	34.5	32.5	33.8	32.9	34.0	34.3
12H					32.7	33.9	33.1	34.2	34.5	32.5	33.7	32.9	34.0	34.3
4H 2H					30.5	31.9	30.8	32.1	32.4	30.4	31.8	30.8	32.0	32.3
3H					32.4	33.6	32.7	33.9	34.2	32.3	33.5	32.7	33.8	34.1
4H					33.2	34.3	33.6	34.6	34.9	33.1	34.2	33.5	34.5	34.8
6H					33.7	34.7	34.1	35.0	35.4	33.6	34.5	34.0	34.9	35.2
8H					33.8	34.7	34.3	35.1	35.5	33.7	34.5	34.1	34.9	35.3
12H					33.9	34.7	34.3	35.1	35.5	33.7	34.5	34.1	34.9	35.3
8H 4H					33.5	34.4	33.9	34.7	35.1	33.4	34.3	33.8	34.6	35.0
6H					34.1	34.9	34.6	35.3	35.7	34.0	34.7	34.4	35.1	35.5
8H					34.3	34.9	34.7	35.4	35.8	34.1	34.8	34.6	35.2	35.6
12H					34.4	34.9	34.8	35.4	35.8	34.2	34.7	34.6	35.2	35.6
12H 4H					33.5	34.3	33.9	34.7	35.1	33.4	34.2	33.8	34.6	35.0
6H					34.1	34.8	34.6	35.2	35.7	34.0	34.7	34.5	35.1	35.5
8H					34.3	34.9	34.8	35.3	35.8	34.2	34.7	34.6	35.2	35.6
Variations with the observer position at spacings:														
S = 1.0H					+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H					+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H					+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117 Corrected 24756 lm Total Lamp Luminous Flux. (8log(F/F0) = 11.1)

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: chen xue chang
 Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity: 65.0%
 Test Distance: 7.400m [K=1.0000]
 Remarks:


```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:7.400m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 300 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.3$	PROTECTION ANGLE:




C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.400m [K=1.0000]
Remarks:

AAI Figure

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 300 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.3$	PROTECTION ANGLE:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.400m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 300 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.3$	PROTECTION ANGLE:



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: chen xue chang
 Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity: 65.0%
 Test Distance: 7.400m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.400m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:7.400m [K=1.0000]
Remarks:

```