


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm		
NAME: LED Flood Light	TYPE:LED	WEIGHT:N/A
SPEC.:N/A	DIM.: 367.0*466.1*54.0mm	SERIAL No.:N/A
MFR.:	SUR.:L393*W321mm	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 141.16 lm/W			
MODEL	TG04-200W-110*40D	I <sub>max</sub> (cd)	23793	S/MH(C0/180)	1.26
NOMINAL POWER(W)	200	LOR(%)	100.0	S/MH(C90/270)	1.05
RATED VOLTAGE(V)	230	TOTAL FLUX(lm)	28410	η UP,DN(C0-180)	0.0,74.7
NOMINAL FLUX(lm)	28409.5	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,25.2
LAMPS INSIDE	1	η up(%)	0.1	CIBSE SHR NOM	1.75
TEST VOLTAGE(V)	230	η down(%)	99.9	CIBSE SHR MAX	1.75

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:24.9DEG  
 Operators:Link Chai  
 Test Date:2022-04-14

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
 Humidity:60%  
 Test Distance:1.900m [K=1.2828]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	589.6	593.5	603.8	590.6	591.5	578.2	560.5	573.8	0- 10	563.8	563.8	1.98,1.98
20	556.3	633.1	765.8	645.8	561.9	505.3	473.6	500.5	10- 20	1642	2205	7.76,7.76
30	499.2	742.2	956.8	781.1	508.8	433.8	406.9	431.4	20- 30	2713	4919	17.3,17.3
40	421.7	867.2	1207	945.5	436.7	365.8	320.0	365.3	30- 40	3776	8695	30.6,30.6
50	331.0	1083	1581	1184	363.7	283.5	276.9	286.9	40- 50	4995	13690	48.2,48.2
60	231.9	1368	2064	1390	262.0	205.9	219.1	211.5	50- 60	6659	20349	71.6,71.6
70	118.9	505.3	725.7	459.5	126.0	114.8	123.8	119.7	60- 70	6217	26567	93.5,93.5
80	31.59	68.17	104.1	65.71	31.43	31.63	36.27	33.47	70- 80	1619	28186	99.2,99.2
90	0.2601	0.3356	1.620	2.055	0.1336	0.5143	0.7014	0.4449	80- 90	192.5	28378	99.9,99.9
100	0.1333	0.0912	0.0960	0.1059	0.2140	0.8088	1.114	0.7292	90-100	4.012	28382	99.9,99.9
110	0.2054	0.1298	0.1237	0.1388	0.2532	0.8032	0.8978	0.6461	100-110	4.323	28387	99.9,99.9
120	0.2893	0.1824	0.1804	0.2005	0.3137	0.7038	0.8646	0.6390	110-120	3.884	28391	99.9,99.9
130	0.3889	0.2537	0.2461	0.2588	0.4594	0.7784	1.026	0.8408	120-130	4.229	28395	99.9,99.9
140	0.5015	0.3192	0.3048	0.3432	0.6587	0.9350	1.080	1.033	130-140	4.543	28399	100,100
150	0.6209	0.4189	0.3952	0.4340	0.7835	0.9562	0.9783	0.9932	140-150	4.221	28404	100,100
160	0.6776	0.5491	0.4770	0.5415	0.8381	0.9569	0.8262	0.8634	150-160	3.230	28407	100,100
170	0.7386	0.6230	0.5334	0.5649	0.9360	0.8759	0.7578	0.7107	160-170	2.005	28409	100,100
180	0.9023	0.7764	0.6839	0.6837	0.8936	0.7538	0.6954	0.6842	170-180	0.6804	28410	100,100
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

Conical surface Flux(90deg): 11016 lm

%lum = 38.8%

%lamp = 38.8%

Conical surface Flux(120deg): 20349 lm

%lum = 71.6%


%lamp = 71.6%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:24.9DEG  
 Operators:Link Chai  
 Test Date:2022-04-14

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
 Humidity:60%  
 Test Distance:1.900m [K=1.2828]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm		
NAME: LED Flood Light	TYPE:LED	WEIGHT:N/A
SPEC.:N/A	DIM.: 367.0*466.1*54.0mm	SERIAL No.:N/A
MFR.:	SUR.:L393*W321mm	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	89634	250347
80	181933	599693
75	269826	1066553
70	347495	2121745
65	408025	3905235
60	463710	4127401
55	495256	3220493
50	515019	2459042
45	533981	1948565

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:24.9DEG  
Operators:Link Chai  
Test Date:2022-04-14

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
Humidity:60%  
Test Distance:1.900m [K=1.2828]  
Remarks:

## WEC AND CCEC

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm					
NAME: LED Flood Light			TYPE:LED		WEIGHT:N/A
SPEC.:N/A			DIM.: 367.0*466.1*54.0mm		SERIAL No.:N/A
MFR.:			SUR.:L393*W321mm		Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.327	.186	.059	.319	.182	.058	.306	.176	.056	.294	.169	.054	.282	.164	.053	
2.0	.317	.174	.053	.311	.171	.053	.299	.166	.052	.288	.161	.051	.277	.157	.049	
3.0	.296	.158	.047	.291	.156	.047	.280	.152	.046	.270	.148	.045	.261	.144	.045	
4.0	.274	.142	.042	.269	.141	.042	.259	.138	.041	.251	.135	.041	.242	.132	.040	
5.0	.253	.129	.037	.248	.127	.037	.240	.125	.037	.232	.122	.036	.224	.120	.036	
6.0	.233	.117	.034	.229	.116	.033	.222	.114	.033	.215	.112	.033	.208	.109	.033	
7.0	.216	.107	.030	.213	.106	.030	.206	.104	.030	.199	.102	.030	.193	.100	.030	
8.0	.201	.098	.028	.198	.097	.027	.191	.096	.027	.186	.094	.027	.180	.093	.027	
9.0	.187	.091	.025	.184	.090	.025	.179	.088	.025	.174	.087	.025	.169	.086	.025	
10.0	.175	.084	.023	.172	.083	.023	.168	.082	.023	.163	.081	.023	.158	.080	.023	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.191	.191	.191	.164	.164	.164	.112	.112	.112	.064	.064	.064	.020	.020	.020	
1.0	.182	.157	.134	.156	.135	.115	.107	.093	.080	.061	.054	.046	.020	.017	.015	
2.0	.176	.133	.096	.151	.114	.083	.104	.079	.058	.060	.046	.034	.019	.015	.011	
3.0	.170	.115	.071	.146	.099	.062	.100	.069	.043	.058	.040	.026	.019	.013	.008	
4.0	.164	.102	.055	.141	.088	.048	.097	.062	.034	.056	.036	.020	.018	.012	.007	
5.0	.157	.092	.045	.135	.080	.039	.093	.056	.027	.054	.033	.016	.017	.011	.005	
6.0	.150	.084	.037	.129	.073	.032	.089	.051	.023	.052	.030	.014	.017	.010	.004	
7.0	.143	.077	.032	.123	.067	.028	.085	.047	.020	.049	.028	.012	.016	.009	.004	
8.0	.136	.072	.028	.117	.062	.024	.081	.044	.017	.047	.026	.010	.015	.008	.003	
9.0	.130	.067	.025	.112	.058	.021	.077	.041	.015	.045	.024	.009	.015	.008	.003	
10.0	.123	.063	.022	.106	.054	.019	.074	.038	.014	.043	.023	.008	.014	.007	.003	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:24.9DEG  
 Operators:Link Chai  
 Test Date:2022-04-14

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
 Humidity:60%  
 Test Distance:1.900m [K=1.2828]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm											
NAME: LED Flood Light					TYPE:LED			WEIGHT:N/A			
SPEC.:N/A					DIM.: 367.0*466.1*54.0mm			SERIAL No.:N/A			
MFR.:					SUR.:L393*W321mm			Shielding Angle:N/A			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		37.9	39.6	38.2	39.8	40.1	46.2	47.9	46.4	48.1	48.3
	3H	38.4	40.0	38.7	40.2	40.5	47.9	49.4	48.2	49.7	49.9
	4H	38.4	39.9	38.7	40.2	40.4	47.9	49.4	48.2	49.7	49.9
	6H	38.4	39.8	38.7	40.0	40.3	47.9	49.2	48.2	49.5	49.8
	8H	38.3	39.7	38.7	40.0	40.3	47.8	49.2	48.2	49.4	49.7
	12H	38.3	39.6	38.6	39.9	40.2	47.8	49.0	48.1	49.4	49.7
4H	2H	41.4	42.9	41.7	43.1	43.4	46.5	48.0	46.8	48.3	48.5
	3H	41.7	43.0	42.0	43.3	43.6	48.3	49.6	48.7	49.9	50.2
	4H	41.7	42.8	42.0	43.2	43.5	48.4	49.6	48.8	49.9	50.2
	6H	41.6	42.7	42.0	43.0	43.4	48.4	49.4	48.8	49.8	50.1
	8H	41.6	42.5	42.0	42.9	43.3	48.3	49.3	48.8	49.7	50.1
	12H	41.5	42.4	42.0	42.8	43.2	48.3	49.2	48.7	49.6	50.0
8H	4H	42.1	43.0	42.5	43.4	43.8	48.3	49.3	48.7	49.6	50.0
	6H	42.1	42.9	42.5	43.3	43.7	48.3	49.1	48.7	49.5	49.9
	8H	42.1	42.8	42.5	43.2	43.6	48.3	49.0	48.7	49.4	49.9
	12H	42.0	42.6	42.5	43.1	43.6	48.3	48.9	48.7	49.3	49.8
12H	4H	42.1	42.9	42.5	43.3	43.7	48.2	49.1	48.7	49.5	49.9
	6H	42.1	42.8	42.5	43.2	43.6	48.3	49.0	48.7	49.4	49.8
	8H	42.1	42.7	42.5	43.1	43.6	48.3	48.9	48.7	49.3	49.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.4					
1.5H	+ 0.7 / - 0.8					+ 1.7 / - 1.6					
2.0H	+ 1.2 / - 2.7					+ 2.4 / - 3.7					

CIE Pub.117, 28410 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 11.6$ )

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:24.9DEG  
 Operators:Link Chai  
 Test Date:2022-04-14

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
 Humidity:60%  
 Test Distance:1.900m [K=1.2828]  
 Remarks:

## UTILIZATION FACTORS TABLE

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm		
NAME: LED Flood Light	TYPE:LED	WEIGHT:N/A
SPEC.:N/A	DIM.: 367.0*466.1*54.0mm	SERIAL No.:N/A
MFR.:	SUR.:L393*W321mm	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	49	36	28	48	36	28	47	35	28	21
0.80	60	46	38	59	46	38	57	45	37	29
1.00	69	56	48	68	56	48	65	57	47	39
1.25	77	65	57	76	64	56	73	63	56	47
1.50	83	72	63	81	71	63	78	69	62	53
2.00	91	82	74	89	80	73	86	78	72	63
2.50	96	87	81	94	86	80	90	83	78	69
3.00	100	93	87	98	91	85	94	88	83	74
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	103	99	106	101	97	101	97	94	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:24.9DEG  
 Operators:Link Chai  
 Test Date:2022-04-14

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
 Humidity:60%  
 Test Distance:1.900m [K=1.2828]  
 Remarks:

# ISOCANDELA DIAGRAM

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm		
NAME: LED Flood Light	TYPE:LED	WEIGHT:N/A
SPEC.:N/A	DIM.: 367.0*466.1*54.0mm	SERIAL No.:N/A
MFR.:	SUR.:L393*W321mm	Shielding Angle:N/A




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 24.9DEG  
Operators: Link Chai  
Test Date: 2022-04-14

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
Humidity: 60%  
Test Distance: 1.900m [K=1.2828]  
Remarks:

### AAI Figure

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm		
NAME: LED Flood Light	TYPE:LED	WEIGHT:N/A
SPEC.:N/A	DIM.: 367.0*466.1*54.0mm	SERIAL No.:N/A
MFR.:	SUR.:L393*W321mm	Shielding Angle:N/A




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:24.9DEG  
 Operators:Link Chai  
 Test Date:2022-04-14

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
 Humidity:60%  
 Test Distance:1.900m [K=1.2828]  
 Remarks:



Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:24.9DEG  
Operators:Link Chai  
Test Date:2022-04-14

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
Humidity:60%  
Test Distance:1.900m [K=1.2828]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:230.04V I:0.8987A P:201.26W PF:0.9735 Freq:50.00Hz Lamp Flux:28409.5x1 lm		
NAME: LED Flood Light	TYPE:LED	WEIGHT:N/A
SPEC.:N/A	DIM.: 367.0*466.1*54.0mm	SERIAL No.:N/A
MFR.:	SUR.:L393*W321mm	Shielding Angle:N/A

Table--1

UNIT: x10cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	600	599	598	597	596	595	595	594	600	599	598	597	596	595	595	594			
5	597	596	595	595	595	593	592	590	598	597	595	592	590	590	591	591			
10	590	589	594	600	604	599	591	584	592	588	578	567	561	564	574	582			
15	576	579	598	643	667	646	600	576	579	571	547	522	513	519	542	565			
20	556	566	633	728	766	736	646	565	562	546	505	480	474	478	501	539			
25	530	552	689	812	861	828	712	561	538	513	465	451	447	450	462	505			
30	499	546	742	895	957	919	781	572	509	473	434	417	407	417	431	466			
35	462	551	799	987	1070	1024	857	596	474	430	403	373	361	375	402	424			
40	422	565	867	1110	1207	1162	945	627	437	388	366	331	320	332	365	385			
45	378	586	956	1270	1378	1341	1051	661	398	350	325	296	293	298	327	349			
50	331	619	1083	1495	1581	1570	1184	699	364	310	283	274	277	277	287	309			
55	284	653	1254	1800	1847	1900	1333	719	325	264	244	253	258	256	249	263			
60	232	620	1368	2204	2064	2273	1390	651	262	217	206	216	219	220	212	216			
65	172	451	1122	2283	1650	2239	1084	460	188	168	162	168	172	171	167	168			
70	119	207	505	1088	726	1024	460	199	126	121	115	121	124	124	120	121			
75	69.8	85.9	188	354	276	337	174	84.9	71.9	71.6	69.1	75.0	77.2	77.6	73.1	72.9			
80	31.6	41.3	68.2	117	104	110	65.7	40.8	31.4	32.0	31.6	35.5	36.3	36.5	33.5	33.5			
85	7.81	11.1	16.2	24.1	21.8	22.7	15.5	10.7	7.47	7.64	7.86	9.62	9.35	10.1	8.58	8.48			
90	0.26	0.40	0.34	0.25	1.62	1.80	2.06	1.48	0.13	0.24	0.51	0.74	0.70	0.66	0.44	0.25			
95	0.11	0.09	0.08	0.08	0.08	0.09	0.11	0.10	0.17	0.33	0.68	0.88	0.93	0.85	0.60	0.30			
100	0.13	0.10	0.09	0.09	0.10	0.09	0.11	0.11	0.21	0.42	0.81	1.03	1.11	1.00	0.73	0.38			
105	0.17	0.12	0.11	0.11	0.11	0.11	0.11	0.13	0.24	0.47	0.83	1.00	1.06	0.92	0.72	0.41			
110	0.21	0.14	0.13	0.13	0.12	0.14	0.14	0.15	0.25	0.48	0.80	0.85	0.90	0.79	0.65	0.39			
115	0.24	0.17	0.16	0.15	0.15	0.16	0.18	0.19	0.27	0.47	0.73	0.76	0.84	0.74	0.59	0.38			
120	0.29	0.20	0.18	0.18	0.18	0.19	0.20	0.23	0.31	0.49	0.70	0.74	0.86	0.78	0.64	0.45			
125	0.34	0.24	0.21	0.21	0.21	0.22	0.23	0.29	0.39	0.56	0.73	0.80	0.95	0.88	0.75	0.55			
130	0.39	0.29	0.25	0.25	0.25	0.25	0.26	0.33	0.46	0.64	0.78	0.86	1.03	0.99	0.84	0.64			
135	0.45	0.35	0.28	0.28	0.28	0.29	0.30	0.36	0.57	0.72	0.85	0.91	1.06	1.06	0.94	0.74			
140	0.50	0.39	0.32	0.30	0.30	0.32	0.34	0.38	0.66	0.78	0.94	0.95	1.08	1.10	1.03	0.82			
145	0.55	0.42	0.37	0.33	0.34	0.36	0.38	0.43	0.74	0.84	0.97	0.98	1.06	1.12	1.05	0.91			
150	0.62	0.48	0.42	0.38	0.40	0.42	0.43	0.48	0.78	0.82	0.96	0.95	0.98	1.03	0.99	0.94			
155	0.65	0.54	0.48	0.47	0.45	0.48	0.49	0.52	0.80	0.80	0.96	0.92	0.89	0.90	0.92	0.91			
160	0.68	0.58	0.55	0.49	0.48	0.51	0.54	0.54	0.84	0.83	0.96	0.90	0.83	0.82	0.86	0.87			
165	0.69	0.59	0.61	0.51	0.50	0.53	0.56	0.55	0.90	0.88	0.93	0.89	0.78	0.75	0.77	0.83			
170	0.74	0.62	0.62	0.54	0.53	0.56	0.56	0.57	0.94	0.93	0.88	0.86	0.76	0.71	0.71	0.76			
175	0.79	0.66	0.68	0.61	0.60	0.61	0.62	0.61	0.88	0.88	0.82	0.82	0.73	0.72	0.72	0.71			
180	0.90	0.75	0.78	0.70	0.68	0.69	0.68	0.69	0.89	0.89	0.75	0.77	0.70	0.68	0.68	0.68			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:24.9DEG  
Operators:Link Chai  
Test Date:2022-04-14

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.366  
Humidity:60%  
Test Distance:1.900m [K=1.2828]  
Remarks: